



MOWER SPECIFICATIONS

MAVERICK TSC MODEL

KOHLER® 747cc

Cutting Width	6000/60"
Cutting Height	1.5"–4.5" with Deck Height Control System
Blades	6000/1/4" x 2 1/2" x 20 1/2", High Lift, Heat Treated
Lift and Height Adjustment	Instant Lift Electronic Actuator
Blade Belt	Single V-Belt Spring Tension
Anti-Scalp Rollers	6000/6 Total (4 Front, 2 Rear)
Deck Flotation	Floats on (4) 1/4" Deck Hangers
Deck Thickness	3/16" Thick Solid Steel
ENGINE	
Gross Horsepower	747cc Air-Cooled Kohler Confidant
Cylinders	V-Twin
Displacement	747 cc
Maximum Torque	42.4 ft. lbs. @ 2600 RPM
Fuel Requirement	Unleaded Gasoline (87 Octane or higher)
Fuel Capacity	6.5 Gallons
Fuel Filter	Replaceable Automotive Type
Cooling System	Air-Cooled
Ignition	Electronic
Starter	12 Volt
Charging System	20 amp
DRIVE SYSTEM	
Transmission	Hydro-Gear® 3200 Dual Integrated Hydrostatic Transaxle
Pump Drive	Integrated Axial Piston Pump & Motor w/Gear Reduction
Wheel Drive	Integrated with Commercial Grade Gear Reduction
Hydrostatic System Oil	20W50 Motor Oil
Hydraulic Filter	25 Micron, Replaceable Spin-On Type, 1 Per Axle
Pumps (2)	10cc Pump and Motor Integrated in one unit
Hydraulic Coolers (2)	7" Cooling Fan per Unit
Weight	925 lbs.
Overall Height	49"
Overall Width	61 1/2"
Overall Length	75"
Tire to Tire Width	46 1/2"
Tires—Front	13 x 6.5–6 Smooth Tread
Tires—Rear	23 x 10.5–12 Turf Tread
Steering	Dual Lever Steering, Independent Control
Turning Radius	Zero Degree, Turns Within Unit Length
Ground Speed (forward)	Up to 9 mph
Parking Brake	Internal Parking Brake

SPECIFICATIONS ARE SUBJECT TO CHANGE.

We're constantly improving our products! For the latest videos, specifications, model improvements and information, please see us at www.badboymowers.com. Not responsible for typographical errors. ©2018. Bad Boy, Inc., All Rights Reserved.