



MOWER SPECIFICATIONS

ZT ELITE TSC MODELS

KOHLER 747cc

KOHLER 725cc

Cutting Width	6000/60"	4800/48"
Cutting Height	1.5"–4.5" with Deck Height Control System	1.5"–4.5" with Deck Height Control System
Blades	6000/1/4" x 2 1/2" x 20 1/2", High Lift, Heat Treated	4800/1/4" x 2 1/2" x 16 1/2", High Lift, Heat Treated
Lift and Height Adjustment	Instant Lift Electronic Actuator	Instant Lift Electronic Actuator
Blade Belt	Single V-Belt Spring Tension	Single V-Belt Spring Tension
Anti-Scalp Rollers	6000/6 Total (4 Front, 2 Rear)	4800/4 Total (2 On Front, 2 In Rear)
Deck Flotation	Floats on (4) 1/4" Deck Hangers	Floats on (4) 1/4" Deck Hangers
Deck Thickness	3/16" Thick Solid Steel	3/16" Thick Solid Steel
ENGINE		
Gross Horsepower	747cc Air-Cooled Kohler Pro 7000	725cc Air-Cooled Kohler Pro 7000
Cylinders	90 Degree V-Twin	90 Degree V-Twin
Displacement	747 cc	725 cc
Maximum Torque	41.3 ft. lbs. @ 2400 RPM	41.3 ft. lbs. @ 2400 RPM
Fuel Requirement	Unleaded Gasoline (87 Octane or higher)	Unleaded Gasoline (87 Octane or higher)
Fuel Capacity	6.5 Gallons	6.5 Gallons
Fuel Filter	Replaceable In-Line Filter	Replaceable In-Line Filter
Cooling System	Air-Cooled	Air-Cooled
Ignition	Electronic	Electronic
Starter	12 Volt	12 Volt
Charging System	16 amp	16 amp
DRIVE SYSTEM		
Transmission	Hydro-Gear® 3100 Dual Integrated Hydrostatic Transaxle	Hydro-Gear® 3100 Dual Integrated Hydrostatic Transaxle
Pump Drive	Integrated Axial Piston Pump & Motor w/Gear Reduction	Integrated Axial Piston Pump & Motor w/Gear Reduction
Wheel Drive	Integrated with Commercial Grade Gear Reduction	Integrated with Commercial Grade Gear Reduction
Hydrostatic System Oil	20W50 Motor Oil	20W50 Motor Oil
Hydraulic Filter	25 Micron, Replaceable Spin-On Type, 1 Per Axle	25 Micron, Replaceable Spin-On Type, 1 Per Axle
Pumps (2)	10cc Pump and Motor Integrated in one unit	10cc Pump and Motor Integrated in one unit
Hydraulic Coolers (2)	7" Cooling Fan per Unit	7" Cooling Fan per Unit
Weight	6000/838 lbs.	4800/783 lbs
Overall Height	46"	46"
Overall Width	6000/61 1/2"	4800/49 1/2"
Overall Length	78"	77"
Tire to Tire Width	46"	46"
Tires—Front	13 x 6.5–6 Smooth Tread	13 x 6.5–6 Smooth Tread
Tires—Rear	6000/22 x 11–10 Turf Tread	4800/22 x 10–10 Turf Tread
Steering	Dual Lever Steering, Independent Control	Dual Lever Steering, Independent Control
Turning Radius	Zero Degree, Turns Within Unit Length	Zero Degree, Turns Within Unit Length
Ground Speed (forward)	Up to 7 mph	Up to 7 mph
Parking Brake	Internal Parking Brake	Internal Parking Brake

SPECIFICATIONS ARE SUBJECT TO CHANGE.

We're constantly improving our products! For the latest videos, specifications, model improvements and information, please see us at www.badboymowers.com. Not responsible for typographical errors. ©2018. Bad Boy, Inc., All Rights Reserved.